

หัวฉีดแบบทัวไป

Flat spray pattern



Features


Very high impact flat spray pattern with narrow spray angle, sharply defined edges and uniform spray distribution. Medium-sized drops. Solid one-piece design with deflector plane. Large unobstructed flow passage minimizes clogging.



Application

- Crushed stone gravel washing Degreasing
- Fruit/vegetable washing High impact washing
- Paper machine deckle spray

Dimension



Specifications

Model	Spray Code	Nozzle Inlet Conn. NPT or BSPT					Spray Capacity (l/min)								Orifice dia. (mm)	Spray Angle (°)			Dimensions		
		1/8	1/4	3/8	1/2	3/4	1 bar	2 bar	3 bar	4 bar	5 bar	6 bar	7 bar	10 bar		1 bar	2 bar	3 bar	L (mm)	A Deflection angle	H Square bar size (mm)
FHC	AJ						2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	2.0	34	50	60	31	60°	15.9
	BE		/	/			5.7	8.1	9.9	11.4	12.7	14.0	15.1	18.0	2.8	42	50	59	41.5	42°	91.1
	DJ		/	/			9.1	12.9	15.8	18.2	20.0	22.0	24.0	29.0	3.6	39	50	60	47	45°	19.1
	FJ		/	/			13.7	19.3	24.0	27.0	31.0	33.0	36.0	43.0	4.8	42	50	53	55	37°	25.4
	AJJ		/	/			23.0	32.0	39.0	46.0	51.0	56.0	60.0	72.0	6.0	43	50	55	72	40°	31.8
	ABE		/	/			28.0	40.0	49.0	57.0	64.0	70.0	75.0	90.0	6.7	38	50	59	72	38°	31.8
	AFJ		/	/			36.0	52.0	63.0	73.0	82.0	89.0	96.0	115.0	7.5	44	50	55	72	37°	31.8
	BJJ		/	/			46.0	64.0	79.0	91.0	102.0	112.0	121.0	144.0	8.3	46	50	53	72	32°	31.8
	DJ		/	/			9.1	12.9	15.8	18.2	20.0	22.0	24.0	29.0	3.6	31	40	50	60.3	35°	22.2
	EJ		/	/			11.4	16.1	19.7	23.0	25.0	28.0	30.0	36.0	4.0	31	40	49	63.5	33°	25.4
	FJ		/	/			13.7	19.3	24.0	27.0	31.0	33.0	36.0	43.0	4.4	32	40	49	72	33°	25.4
	GJ		/	/			16.0	23.0	28.0	32.0	36.0	39.0	42.0	50.0	5.2	32	40	49	75.5	29°	25.4
	HJ		/	/			18.2	26.0	32.0	36.0	41.0	45.0	48.0	58.0	5.2	32	40	48	77.0	26°	25.4
	IJ		/	/			21.0	29.0	36.0	41.0	46.0	50.0	54.0	65.0	5.6	34	40	44	77.0	28°	25.4
	AJJ		/	/			23.0	32.0	39.0	46.0	51.0	56.0	60.0	72.0	6.0	35	40	44	86.5	28°	25.4
	JD	/					0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	1.2	20	35	41	23.0	40°	11.1
	AJ	/	/				2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	2.0	18	35	39	36.5	36°	15.9
	BJ	/	/				4.6	6.4	7.9	9.1	10.2	11.2	12.1	14.4	2.8	24	35	40	42.0	30°	19.1
	BE	/	/				5.7	8.1	9.9	11.4	12.7	14.0	15.1	18.0	2.8	24	35	39	39.0	28°	19.1
	CJ	/	/				6.8	9.7	11.8	13.7	15.3	16.7	18.1	22.0	3.2	26	35	41	52.5	28°	19.1
	DJ	/	/				9.1	12.9	15.8	18.2	20.0	22.0	24.0	29.0	3.6	28	35	38	58.0	26°	22.2
	EJ	/	/				11.4	16.1	19.7	23.0	25.0	28.0	30.0	36.0	4.0	31	35	38	63.5	23°	22.2
	FJ	/	/				13.7	19.3	24.0	27.0	31.0	33.0	36.0	43.0	4.4	29	35	39	73.0	27°	25.4
	HJ	/	/				18.2	26.0	32.0	36.0	41.0	45.0	48.0	58.0	5.2	26	35	40	81.0	24°	25.4
AJJ	/	/				23.0	32.0	39.0	46.0	51.0	56.0	60.0	72.0	6.0	26	35	40	89.0	19°	25.4	
AFJ	/	/				36.0	52.0	63.0	73.0	82.0	89.0	96.0	115.0	7.5	26	35	40	114.0	23°	31.8	
BJJ	/	/				46.0	64.0	79.0	91.0	102.0	112.0	121.0	144.0	8.3	25	35	40	122.0	22°	31.8	
DJ	/	/				9.1	12.9	15.8	18.2	20.0	22.0	24.0	29.0	3.6	15	25	34	65.0	25°	19.1	
AJ	/	/				2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	2.0		15	23	47.5	22°	15.9	
BJ	/	/				4.6	6.4	7.9	9.1	10.2	11.2	12.1	14.4	2.8		15	19	54.0	19°	15.9	
CJ	/	/				6.8	9.7	11.8	13.7	15.3	16.7	18.1	22.0	3.2	6	15	24	72.0	25°	19.1	
DJ	/	/				9.1	12.9	15.8	18.2	20.0	22.0	24.0	29.0	3.6	8	15	21	92.0	18°	22.2	
EJ	/	/				11.4	16.1	19.7	23.0	25.0	28.0	30.0	36.0	4.4	9	15	20	90.5	15°	22.2	
FJ	/	/				13.7	19.3	24.0	27.0	31.0	33.0	36.0	43.0	5.2	10	15	19	125.0	14°	25.4	
HJ	/	/				18.2	26.0	32.0	36.0	41.0	45.0	48.0	58.0	6.0	11	15	18	130.0	14°	25.4	
AJJ	/	/				23.0	32.0	39.0	46.0	51.0	56.0	60.0	72.0	7.5	11	15	18	137.0	14°	25.4	
BJJ	/	/				46.0	64.0	79.0	91.0	102.0	112.0	121.0	144.0	8.3	12	15	18	191.0	14°	31.8	

How to order Please order for a specific nozzle on this coding system (Example)

3/8"

Pipe Size

FHC

Model

45

Spray Angle

DJ

Spray Code

S303

Material